

AMA Specifications—Passenger Car

MAKE OF CAR Pontiac	MODEL YEAR 1967	DATE ISSUED 12-23-66 REVISED ¹⁰¹			
MODEL	FIREBIRD	FIREBIRD SPRINT	FIREBIRD 326	FIREBIRD H. O.	FIREBIRD 400

DRIVE UNITS—TRANSMISSIONS

Manual 3-speed (std. or opt.)	Standard
Manual 4-speed (std. or opt.)	Optional
Manual with overdrive (std. or opt.)	Not Offered
Automatic (std. or opt.)	Optional

DRIVE UNITS—MANUAL TRANSMISSION

Number of forward speeds	3-SPEED (a)			4-SPEED		
	6-Cyl.	326 V-8	400 V-8	6-Cyl.	V-8	
Transmission ratios	In first	2.85:1	2.54:1	2.41:1	3.11:1 (b)	2.52:1
	In second	1.68:1	1.50:1	1.59:1	2.20:1 (b)	1.88:1
	In third	1.00:1	1.00:1	1.00:1	1.47:1 (b)	1.46:1
	In fourth	--	--	--	1.00:1 (b)	1.00:1
	In reverse	2.95:1	2.63:1	2.41:1	3.11:1 (b)	2.59:1
Synchronous meshing, specify gears	All Forward					
Shift lever location	Steering Column (a)			Floor		
Lubricant	Capacity (pt.)	2.8			2.5	
	Type recommended	Type A - Extreme Pressure				
	SAE viscosity number	Summer	80 or 90			
		Winter	80 or 90			
		Extreme cold	80 or 90			

DRIVE UNITS—MANUAL TRANSMISSION WITH OVERDRIVE

For transmission data see manual transmission section

Type (planetary or other)	Not Offered	
Manual lockout (yes, no)		
Downshift accelerator control (yes, no)		
Minimum cut-in speed		
Gear ratio		
Lubricant	Capacity (pt.) (Overdrive only)	
	Separate filler (yes, no)	
	Type recommended	
	SAE viscosity number	Summer
		Winter
Extreme cold		

- (a) Floor shift available with 3-speed manual transmissions.
- (b) 4-Speed not available with 6 cyl. 1-bbl. carb. engine.