MODEL 3030 VBLH LIQUID HONING MACHINE

STANDARD DOOR DESIGN:

HINGED HORIZONTAL SWINGING, FITTED WITH AN INTERIOR SLURRY CONTAINMENT DRAIN SYSTEM. ELECTRICAL INTERLOCK SYSTEM TO PREVENT BLAST OPERATION WHEN DOOR IS OPEN. MACHINE WIDTH: 58" WITH DOOR OPEN

OPTIONAL DOOR DESIGN (SHOWN)

VERTICAL SLIDING COUNTERBALANCED, REDUCES FLOOR SPACE REQUIREMENT. ELECTRICAL INTERLOCK SYSTEM TO PREVENT BLAST OPERATION WHEN DOOR IS OPEN.

NOTES:

1. BLAST CABINET: #12 GAUGE STANDARD: HOT ROLLED STEEL
   HOPPER: #10 GAUGE OPTIONAL: STAINLESS STEEL
2. COMPRESSED AIR REQUIREMENT: 75 CFM @ 80 PSIG
3. WATER REQUIREMENT: NORMAL CITY WATER PRESSURE
4. ELECTRICAL REQUIREMENT: 230/460 VOLT, 3 PHASE, 60 HERTZ
5. WEIGHT: 1000 LBS. APPROXIMATE





TITLE: 3030 VBLH MACHINE SPECIFICATIONS

THIS DRAWING AND DESIGN INCLUDING ALL NOVEL AND PATENTABLE FEATURES SEPARATELY OR COLLECTIVELY DISCLOSED AND INCLUDED THEREIN ARE THE PROPERTY OF THE VAPOR BLAST MFG. CO. AND ARE NOT TO BE COPIED OR USED DIRECTLY OR INDIRECTLY BY ANYBODY WHOMSOEVER WITHOUT THE WRITTEN CONSENT OF SAID COMPANY. THIS DRAWING IS LOANED SUBJECT TO RETURN TO SAID COMPANY UPON THEIR DEMAND.

VAPOR BLAST MANUFACTURING COMPANY
3025 W. ATKINSON AVENUE MILWAUKEE, WI. 53209

DATE: 8-10-93	SUPERSEDES:	SUPERSEDED BY:
DRAWN BY: FB	DWG. NO. B 99-530	
SCALE: NONE		